Mono County Community Development Department

PO Box 3569 Mammoth Lakes, CA 93546 760.924.1800, fax 924.1801 inspection hotline: 760.924.1827 Building Division commdev@mono.ca.gov

PO Box 8 Bridgeport, CA 93517 760.932.5420, fax 932.5431 www.monocounty.ca.gov

APPLICABLE 2010 CALIFORNIA BUILDING CODES AND DESIGN STANDARDS

Administrative Code Fire Code, 2007 Edition Plumbing Code

Electrical Code Green Building Standards Code Referenced Standards Code

Energy Code Historical Building Code Residential Code

Existing Building Code, 2007 Edition Mechanical Code

Building Code, including Appendices: C (Agricultural Buildings) and I (Patio Covers)

SEISMIC DESIGN CATEGORY: "D" CLIMATE ZONE: 16

SOILS DOCUMENTATION: All structures **WIND LOAD:** 90 mph (3 second gust) Exposure "C"

FROST DEPTH: 18" below exterior finished grade minimum

SNOW LOADS:

- High desert area roofs (*): Terrain Category D/Flat unobstructed areas ASCE7-10 Table 7-2 Ce=0.9.
- All other roofs: Terrain Category B/Partially Exposed ASCE7-10 Table 7-2 *Ce* = 1.0.
- All roofs: ASCE-10 Table 7-3 Thermal Factor *Ct* = 1.1.
- All roofs: ASCE-10 Table 71.5-2 Importance Factor $I_s = 1.0$.
- Use Fig. 7-2b graph in ASCE-10 and "All Other Surfaces" curve for determination of Cs if roof meets criteria for slope reduction.

GROUND SNOW LOAD p_g PSF - ROOF SNOW LOAD p_f CONVERSION TABLE			
HIGH DESERT LOCATIONS	ELEVATION	GROUND SNOW LOAD p_g (psf)	FLAT ROOF SNOW LOAD $p_f = (.7)(\frac{0.9^*}{0.9^*} \text{ or } 1.0 = \text{C}_e)(1.1 = \text{C}_t)(1.0 = \text{I})p_g$ = (psf)
Chalfant Valley <mark>*</mark>	4,200 ft	55 psf	38 psf
Hammil Valley <mark>*</mark>	4,500 ft	55 psf	38 psf
Paradise <mark>*</mark>	5,000 ft	55 psf	38 psf
Topaz <mark>*</mark>	5,000 ft	55 psf	38 psf
Coleville <mark>*</mark>	5,100 ft	55 psf	38 psf
Benton <mark>*</mark>	5,400 ft	55 psf	38 psf
Walker <mark>*</mark>	5,400 ft	55 psf	38 psf
Bridgeport	6,470 ft	65 psf	50 psf
Mono City	6,899 ft	75 psf	58 psf
Long Valley (east of US 395)	7,000 ft	80 psf	62 psf
Tom's Place	7,000 ft	80 psf	62 psf
MOUNTAIN AREA LOCATIONS	ELEVATION	GROUND SNOW LOAD p_g (psf)	FLAT ROOF SNOW LOAD p _f =(.7)(1.0=C _e)(1.1=C _t)(1.0=I)p _g = (psf)
Swall Meadows	6,400	100 psf	77 psf
Sonora Junction	6,500	155 psf	119 psf
Rancheria Estates	6,600	105 psf	81 psf
Pickel Meadow	6,800	155 psf	119 psf
Lee Vining	6,800	120 psf	92 psf
Long Valley (west of US 395)	7,000	125 psf	96 psf
Lundy Lake (lower)	7,000	150 psf	116 psf
Crowley Lake	7,000	125 psf	96 psf
Bald Mountain/Arcularius	7,100	150 psf	116 psf
Twin Lakes	7,200	140 psf	109 psf
Devil's Gate	7,400	155 psf	119 psf
Crestview	7,500	150 psf	116 psf
Swauger Creek	7,500	150 psf	116 psf
Convict Lake	7,580	155 psf	119 psf
June Lake	7,600	155 psf	119 psf
Julie Lake	.,		
Lundy Lake (upper)	8,000	285 psf	220 psf